




Belt Skimmer is a Traditional Favorite

- Steel, heavy-duty construction
- Removable, easy-to-clean oil collection tray
- Continuous-duty, fan-cooled motor
- Self-tensioning belt on fixed lower pulley (to 24")
- Hanging lower pulley design (36" and up)
- Dual wiper set with lifetime warranty
- One year warranty all other parts (except steel belts)
- Accessories shown below



Belt Skimmer, Diverter,™ and Lockjaw™ shown here



NEW

Outboard Motor Shaft for longer steel belt life in chemically aggressive applications



| Model | Part Number* | Belt Type | Fluid Max Temp | Capacity | Belt Reach | Belt Width | Required Access |
|---------------------|--------------|---------------------|---------------------|-----------------|------------|------------|-----------------|
| Belt Skimmer | BPF1-08 | Poly | 40-80°F (4-27°C) | 1 gph (3.8 lph) | 8" (20cm) | 1" (25mm) | 2" (50mm) |
| | BPF1-12 | Poly | 40-80°F (4-27°C) | 1 gph (3.8 lph) | 12" (30cm) | 1" (25mm) | 2" (50mm) |
| | BPF1-18 | Poly | 40-80°F (4-27°C) | 1 gph (3.8 lph) | 18" (45cm) | 1" (25mm) | 2" (50mm) |
| | BPF1-24 | Poly | 40-80°F (4-27°C) | 1 gph (3.8 lph) | 24" (60cm) | 1" (25mm) | 2" (50mm) |
| | BPF2-08 | Poly | 40-80°F (4-27°C) | 2 gph (7.8 lph) | 8" (20cm) | 2" (50mm) | 4" (10cm) |
| | BPF2-12 | Poly | 40-80°F (4-27°C) | 2 gph (7.8 lph) | 12" (30cm) | 2" (50mm) | 4" (10cm) |
| | BPF2-18 | Poly | 40-80°F (4-27°C) | 2 gph (7.8 lph) | 18" (45cm) | 2" (50mm) | 4" (10cm) |
| | BPF2-24 | Poly | 40-80°F (4-27°C) | 2 gph (7.8 lph) | 24" (60cm) | 2" (50mm) | 4" (10cm) |
| | BSF1-08 | Steel | 60-212°F (15-100°C) | 1 gph (3.8 lph) | 8" (20cm) | 1" (25mm) | 2" (50mm) |
| | BSF1-12 | Steel | 60-212°F (15-100°C) | 1 gph (3.8 lph) | 12" (30cm) | 1" (25mm) | 2" (50mm) |
| | BSF1-18 | Steel | 60-212°F (15-100°C) | 1 gph (3.8 lph) | 18" (45cm) | 1" (25mm) | 2" (50mm) |
| | BSF1-24 | Steel | 60-212°F (15-100°C) | 1 gph (3.8 lph) | 24" (60cm) | 1" (25mm) | 2" (50mm) |
| | BSF2-08 | Steel | 60-212°F (15-100°C) | 2 gph (7.8 lph) | 8" (20cm) | 2" (50mm) | 4" (10cm) |
| | BSF2-12 | Steel | 60-212°F (15-100°C) | 2 gph (7.8 lph) | 12" (30cm) | 2" (50mm) | 4" (10cm) |
| BSF2-18 | Steel | 60-212°F (15-100°C) | 2 gph (7.8 lph) | 18" (45cm) | 2" (50mm) | 4" (10cm) | |
| BSF2-24 | Steel | 60-212°F (15-100°C) | 2 gph (7.8 lph) | 24" (60cm) | 2" (50mm) | 4" (10cm) | |

*115v motors standard; 220v motors available by adding "E" to end of part number.

*Outboard motor shaft available for steel belt units by replacing the "S" in the part number with "Z".

*Longer reach units available in 1' increments by changing suffix of part number (-36, -48, -60, etc.)

| Accessories | Part Number | Description |
|--------------|------------------|---|
| BGST4 | Diverter | Diverter, oil/water separator for pure oil discharge (raises unit by 2", please account for when selecting reach) |
| BGX2 | Lockjaw | Lockjaw Mounting Clamp affixes skimmer to any 1/4" thick wall or barrel, making portability simple |
| XETIMER | Timer | Timer, 24 hour, 3 settings per day, 110v plugs to any standard outlet |
| XETIMER-GSBZ | Integrated Timer | Integrated Timer, 7 day, 2 hour interval settings, integrated within motor housing |



To determine required reach, measure from mounting point to low fluid operating level

